


NOTE:-

- 1 SIZE - 102.4" LG. X 78.74" WIDTH X 39.37" HT
- EYE PAD THK.-30.00 MM
- EYE PAD HOLE DIA-36.00 MM
- 'D' SHACKEL SIZE-7/8"
- TOTAL WT- 3275.0 KG.
- SR.No-433/15-01



PART LIST

ITEM	DESCRIPTION
1	GATE VALVE, 3.1/16"-10,000 PSI. W.P. FLANGED END, FULL BORE, NON RISING STEM, INCLUDING HANDWHEEL WITH GREASE FITTING.
2	POSITIVE CHOKE, 3.1/16"-10,000 PSI. W.P., 2" MAX. ORIFICE, FLANGED INLET & OUTLET.
2a	ADJUSTABLE CHOKE, 3.1/16"-10,000 PSI. W.P., 2" MAX. ORIFICE, FLANGED INLET & OUTLET.
3	STUDDER CROSS, AS PER API-6A 3.1/16"-10,000 PSI. W.P. FULL BORE TOP & BOTTOM, WITH THREE PORTS
4	STUDDER SPECIAL TEE, (FULL BORE) 3.1/16" X 3.1/16" X 3.1/16"-10,000 PSI. W.P.
5	FLANGE ADAPTER-INLET 3.1/16"-10,000 PSI. W.P. X 3"-FIG. 1502 FEMALE
6	BLIND FLANGE 3.1/16"-10,000 PSI. WITH LEAD
7	FLANGE ADAPTER-OUTLET 3.1/16"-10,000 PSI. W.P. X 3"-FIG. 1502 MALE WITH NUT.
8	SPACER SPOOL, 3.1/16"-10,000 PSI. W.P. FULL BORE
9	NEEDLE VALVE-STRAIGHT TYPE, 10,000 PSI. W.P.
10	PRESSURE GAUGE, RANGE, 0-10,000 PSI., BOTTOM ENTRY
11	THERMOWELL ASSLY. & THERMOMETER
12	SKID ('I' BEAM)
13	LIFTING LUG
14	TOOL BOX.

ITEM	001
ASSLY. NO.	548C-306166-20-05
SERVICE	SOUR

MATERIAL	HEAT TREAT	PLATING/COATING	REV.	DESCRIPTION	APPRO.	DATE
-	-	-				

UNLESS OTHERWISE SPECIFIED,
 1. ALL DIMENSIONS ARE IN MM.
 2. BREAK SHARP EDGES 0.2 R.
 3. UNFINISHED SURFACES SHOULD BE 'V'.
 4. TOLERANCES:
 X = ± 0.50 XXX = ± 0.10
 .XX = ± 0.25 ANGLES = ± 0.30'
 * DIMENSIONS ARE CRITICAL.
 5. DO NOT SCALE DRAWING.

PO #P150210

DMN	K.S.	SKID MOUNTED CHOKE MANIF.
APPRO.	K.M.I.W	3.1/16"-10,000 PSI. W.P.
DATE	25/01/16	
SCALE	NTS.	

PARVEEN INDUSTRIES PVT.
 DRG. No. PE/T/2016/160125-11